



## HinriPress Vario Liquid

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

---

- 1.1 Product identifier**  
Commercial product name: HinriPress Vario Liquid  
Product group: Liquid component  
UFI: Y8SY-219S-M00D-AMU4
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Use of the substance/mixture: Manufacture of dental products.
- 1.3 Details of the supplier of the safety data sheet**  
**Manufacturer:** retec® Kunststofftechnik GmbH  
Street / mailbox: Industriestraße 2  
Country code. / postal code / city: D-61191 Rosbach v.d.H  
Phone: +49 (0) 6007 - 9157 0  
Fax: +49 (0) 6007 - 9157 29  
E-mail: [info@retect-dent.de](mailto:info@retect-dent.de)  
Contact person: Research & Development  
Department  
E-mail: [info@retect-dent.de](mailto:info@retect-dent.de)  
Website: [www.retect-dent.de](http://www.retect-dent.de)
- Supplier:** ERNST HINRICHS Dental GmbH  
Street / mailbox: Borsigstr. 1  
Country code. / postal code / city: D - 38644 Goslar  
Phone: 0 53 21 / 5 06 24  
Fax: 0 53 21 / 5 08 81  
E-mail / Website: [info@hinrichs-dental.de](mailto:info@hinrichs-dental.de) / [www.hinrichs-dental.de](http://www.hinrichs-dental.de)
- 1.4 Emergency telephone number:** +49 (0) 6007-91570

### SECTION 2: Hazards identification

---

- 2.1 Classification of the substance or mixture:**  
**GB CLP Regulation**  
Flam. Liq. 2; H225  
Skin Irrit. 2; H315  
Skin Sens. 1; H317  
STOT SE 3; H335
- Full text of hazard statements: see SECTION 16.
- 2.2 Label elements:**  
**GB CLP Regulation**  
**Hazard components for labelling:** Methyl methacrylate  
1,4-Butandiol dimethacrylate
- Signal word:** Danger
- Pictograms:**
- Hazard statements:**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.



## HinriPress Vario Liquid

H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.

### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P302+P352 IF ON SKIN: Wash with plenty of water and soap.  
P321 Specific treatment (see ... on this label).  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370+P378 In case of fire: Use carbon dioxide (CO<sub>2</sub>), foam or dry powder to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container to as hazardous waste - in accordance with local and national legislation - suitable, approved incinerator for combustible organic waste.

**2.3 Other hazards** No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Chemical characterisation:** Mixture based on methyl methacrylate.

CAS No	Chemical name	Quantity
EC No	Index No	REACH No
Classification (GB CLP Regulation)		
80-62-6	Methyl methacrylate	90 - < 95 %
	201-297-1	01-2119452498-28
	Flam. Liq. 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H224 H315 H317 H335	
2082-81-7	1,4-Butandiol dimethacrylate	5 - < 10 %
	218-218-1	01-2119967415-30
	Skin Sens. 1; H317	

Full text of H- and EUH-phrases: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
80-62-6	201-297-1	Methyl methacrylate	90 - < 95 %
	inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
2082-81-7	218-218-1	1,4-Butandiol dimethacrylate	5 - < 10 %
	dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg		

## SECTION 4: First aid measures

### 4.1 Description of first aid measures:

#### General information:

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs, get medical advice/attention. If eye irritation persists, get medical advice/attention.

#### After inhalation:

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated



## HinriPress Vario Liquid

		clothing and wash it before reuse. In case of skin irritation, consult a physician.
	<b>After contact with eyes:</b>	After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
	<b>After ingestion:</b>	Do NOT induce vomiting. Rinse mouth. Call a physician immediately.
4.2	<b>Most important symptoms and effects, both acute and delayed:</b>	Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.
4.3	<b>Indication of any immediate medical attention and special treatment needed:</b>	Treat symptomatically.

### SECTION 5: Firefighting measures

---

5.1	<b>Extinguishing media:</b>	
	<b>Suitable extinguishing media:</b>	Carbon dioxide (CO <sub>2</sub> ), Foam, Extinguishing powder.
	<b>Unsuitable extinguishing media:</b>	Full water jet.
5.2	<b>Special hazards arising from the substance or mixture:</b>	Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Vapours can form explosive mixtures with air
5.3	<b>Advice for firefighters:</b>	Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.
	<b>Additional information:</b>	Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

---

6.1	<b>Personal precautions, protective equipment and emergency procedures:</b>	Remove all sources of ignition.
6.2	<b>Environmental precautions:</b>	Do not allow to enter into surface water or drains.
6.3	<b>Methods and material for containment and cleaning up:</b>	Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.
6.4	<b>Reference to other sections:</b>	Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

### SECTION 7: Handling and storage

---

7.1	<b>Precautions for safe handling:</b>	
	<b>Advice on safe handling:</b>	When using do not eat, drink, smoke, sniff. Use only in well-ventilated areas. Do not breathe gas/fumes/vapour/spray.
	<b>Advice on protection against fire and explosion:</b>	Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in headspace of closed



## HinriPress Vario Liquid

systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene:** Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

**Further information on handling:** Caution! Transport usually takes place at temperatures above the flash point.

**7.2 Conditions for safe storage, including any incompatibilities**  
**Requirements for storage rooms and vessels:** Keep container tightly closed. Keep in a cool, well-ventilated place. Protect from direct sunlight.

**Advice on storage compatibility:** Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

**Further information on storage conditions:** Keep away from heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50 100	208 416		TWA (8 h) STEL (15 min)	WEL WEL

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
80-62-6	Methyl methacrylate			
	Worker DNEL, long-term	inhalation		208 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal		17 mg/kg bw/day

**8.2 Exposure controls:**  
**Appropriate engineering controls:** If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear eye/face protection.

**Hand protection:** Wear suitable protective gloves. To protect against splashes: butyl; EN 374. For protection against immersion: Butyl; 0.7 mm or stronger, EN 374. The suitability of gloves should be agreed with the manufacturer. In case of contamination or if the breakthrough time is exceeded, change gloves. Resistance of the glove material: see information from the glove manufacturer.

**Skin protection:** Flame-retardant protective clothing. Wear anti-static footwear and clothing.



## HinriPress Vario Liquid

### Respiratory protection:

Wear suitable respiratory protection if technical measures are inadequate or not available and exposure is expected to exceed the DNEL (derived exposure level below which the substance does not cause any adverse effects on human health). A suitable breathing mask with filter type A (EN141 or EN405) is recommended. If particularly high vapour concentrations form, a self-contained breathing apparatus may be necessary.

## SECTION 9: Physical and chemical properties

---

### 9.1 Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic
Melting point/freezing point:	-48 °C
Boiling point or initial boiling point and boiling range:	100,5 °C
Flammability:	not applicable
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	12,5 vol. %
Flash point:	10 °C
Auto-ignition temperature:	421 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility: (at 20 °C)	12,5 g/L
Solubility in other solvents:	not determined
Partition coefficient n-octanol/water:	1,38
Vapour pressure: (at 20 °C)	36 hPa
Density (at 15,5 °C):	0,949 g/cm <sup>3</sup>
Relative vapour density: (at 20 °C)	3,5

### 9.2 Other information

#### Information with regard to physical hazard classes

Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties:	Not oxidising.

#### Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic: (at 20 °C)	0,53 mPa·s

## SECTION 10: Stability and reactivity

---

<b>10.1 Reactivity:</b>	Highly flammable, Vapours can form explosive mixtures with air.
<b>10.2 Chemical stability:</b>	The product is stable under storage at normal ambient temperatures.
<b>10.3 Possibility of hazardous reactions:</b>	Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

# EU - Safety data sheet

according to UK REACH Regulation



Revision date: 15.04.2024

Revision No: 1,07 - Replaces version: 1,06

Date of printing: 19.06.2024

Page: 6 / 10

## HinriPress Vario Liquid

- 10.4 Conditions to avoid:** Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Protect from direct sunlight.
- 10.5 Incompatible materials:** Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.
- 10.6 Hazardous decomposition products** No known hazardous decomposition products.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects:

**Acute toxicity:**

Based on available data, the classification criteria are not met.

**ATEmix tested**

LD50, oral

**Dose**

7870 mg/kg

**Species**

Rat

**Source**

LD50, dermal

> 5000 mg/kg

Rabbit

LC50, inhalative (vapour) (4h)

78 mg/l

Rat

CAS No	Chemical name	Exposure routes	Dose	Species	Source	Method
80-62-6	Methyl methacrylate	oral	LD50 >5000 mg/kg	Rat	OECD 401	
		dermal	LD50 >5000 mg/kg	Rabbit		
		inhalative vapour	LC50 29,8 mg/l	Rat		
2082-81-7	1,4-Butandiol dimethacrylate	oral	LD50 >10000 mg/kg	Rat		
		dermal	LD50 >3000 mg/kg	Rabbit		

**Irritation and corrosivity:**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects:**

May cause an allergic skin reaction. (Methyl methacrylate; 1,4-Butandiol dimethacrylate)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

**STOT-single exposure:**

May cause respiratory irritation. (Methyl methacrylate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard:**

Based on available data, the classification criteria are not met.

**Additional information on tests:**

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].



## HinriPress Vario Liquid

### SECTION 12: Ecological information

#### 12.1 Toxicity Acute (short-term) fish toxicity

CAS No	Chemical name		[h]   [d]	Species	Source	Method
	Aquatic toxicity	Dose				
<b>80-62-6</b>	<b>Methyl methacrylate</b>					
	Acute fish toxicity	LC50 > 79mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 > 110 mg/l	72 h	Selenastrum capricornutum	OECD 201	
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna (Big waterflea)	OECD 202	
<b>2082-81-7</b>	<b>1,4-Butandiol dimethacrylate</b>					
	Acute fish toxicity	LC50 32,5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 7,51 mg/l	48 h	Daphnia magna (Big water flea)	OECD 211	
	Crustacea toxicity	NOEC 7,51 mg/l		Selenastrum capricornutum		

**12.2 Persistence and degradability:** Biodegradable.

**12.3 Bioaccumulative potential:** On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

**12.4 Mobility in soil:** Mobility in soil: No adsorption in soil or sediment.

**12.5 Results of PBT and vPvB assessment:** The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**12.6 Endocrine disrupting properties:** This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7 Other adverse effects:** No information available.

**Further information:** Avoid release to the environment.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods:**  
**Disposal recommendations:** Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products:**

# EU - Safety data sheet

according to UK REACH Regulation



Revision date: 15.04.2024

Revision No: 1,07 - Replaces version: 1,06

Date of printing: 19.06.2024

Page: 8 / 10

## HinriPress Vario Liquid

070208: WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues  
Classified as hazardous waste.

**Contaminated packaging:** Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID):

14.1 **UN number:** UN 1247  
14.2 **UN proper shipping name:** METHYL METHACRYLATE MONOMER, STABILIZED  
14.3 **Transport hazard class(es):** 3  
14.4 **Packing group:** II  
Hazard label: 3  
Classification code: F1  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 339  
Tunnel restriction code: D/E  
**Other applicable information (land transport)** SAPT: > 60 °C

#### Inland waterways transport (ADN)

14.1 **UN number:** UN 1247  
14.2 **UN proper shipping name:** METHYL METHACRYLATE MONOMER, STABILIZED  
14.3 **Transport hazard class(es):** 3  
14.4 **Packing group:** II  
Hazard label: 3  
Classification code: F1  
Limited quantity: 1 L  
Excepted quantity: E2  
**Other applicable information (inland waterways transport)** SAPT: > 60 °C

#### Marine transport (IMDG)

14.1 **UN number:** UN 1247  
14.2 **UN proper shipping name:** METHYL METHACRYLATE MONOMER, STABILIZED  
14.3 **Transport hazard class(es):** 3  
14.4 **Packing group:** II  
Hazard label: 3  
Special Provisions: -  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D  
**Other applicable information (marine transport)** SAPT: > 60 °C

#### Air transport (ICAO-TI/IATA-DGR)

14.1 **UN number:** UN 1247  
14.2 **UN proper shipping name:** METHYL METHACRYLATE MONOMER, STABILIZED  
14.3 **Transport hazard class(es):** 3  
14.4 **Packing group:** II  
Hazard label: 3  
Limited quantity Passenger: 1 L



## EU - Safety data sheet

according to UK REACH Regulation



Revision date: 15.04.2024

Revision No: 1,07 - Replaces version: 1,06

Date of printing: 19.06.2024

Page: 9 / 10

### HinriPress Vario Liquid

Passenger LQ:	Y-341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L
<b>Other applicable information (air transport)</b>	SAPT: > 60 °C

- 14.5 Environmental hazards**  
**ENVIRONMENTALLY HAZARDOUS:** No
- 14.6 Special precautions for user**  
**Warning:** Combustible liquids.
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** not applicable

#### SECTION 15: Regulatory information

##### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 90 % (854,1 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 90 % (854,1 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

- 15.2 Chemical safety assessment** Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

##### 16.1 Abbreviations and acronyms

Flam. Liq:	Flammable liquids
Skin Irrit:	Skin irritation
Skin Sens:	Skin sensitisation
STOT SE:	Specific target organ toxicity - single exposure
ADR:	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road )
IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances

# EU - Safety data sheet

according to UK REACH Regulation



Revision date: 15.04.2024

Revision No: 1,07 - Replaces version: 1,06

Date of printing: 19.06.2024

Page: 10 / 10

## HinriPress Vario Liquid

CAS                      Chemical Abstracts Service  
LC50:                    Lethal concentration, 50%  
LD50:                    Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

### Relevant H and EUH statements (number and full text):

H225      Highly flammable liquid and vapour.  
H315      Causes skin irritation.  
H317      May cause an allergic skin reaction.  
H335      May cause respiratory irritation.

### 16.2 Further Information:

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)